

6. Proportional results showed an increased in CBR values with increase in bagasse fibre percentages to a peak ratio of 7.5% + 7.5% to soil ratio

REFERENCES

- Allam, M. M., and Sridharan, A. (1981). Effect of Repeated Wetting and Drying on Shear Strength. *Journal of Geotechnical Engineering, ASCE*, 107(4):421–438
- Awaji, H.A., (2001). Settlement and Bearing Capacity of Geogrid-Reinforced Sand over Collapsible Soil. *Geotext. Geomembranes*, 19(2): 75-88
- Attoh-Okine, N.O. (1995). Lime Treatment of Laterite Soils and Gravels-Revisited. *Construction and Building Material*, 9(5): 283-287
- Azadegan, O., S.H. Jafari and J. Li, (2012). Compaction Characteristics and Mechanical Properties of Lime/Cement Treated Granular Soils. *Electron. J. Geotech. Eng.*, 17: 2275-2284
- Barisua, E. N., Charles, K., Ode, T., (2018). Comparative Strength Evaluation of Cementitious Stabilizing Agents Blended with Pulverized Bagasse Fibre for Stabilization of Expansive Lateritic Soils. *Global Scientific Journal*, 6(12):220-238
- Charles, K., Isaac, O. A., Terence, T.T. W. (2018). Stabilization of Deltaic Soils Using Costus Afer Bagasse Fibre Ash as Pozzolana. *International Journal of Civil and Structural Engineering Research*. 6(1):133-141
- Charles, K., Amakiri – Whyte, B., Terence, T. T. W. (2018). Stabilization of Black Cotton Clayey Soils with Cementitious Stabilizing Agents Blended with Waste Agricultural Products. *Journal of Scientific and Engineering Research*, 5(12):227-238
- Charles, K., Terence, T. T. W., and Gbinu, S. K., (2018). Stabilization of Niger Deltaic Expansive Clay Soils Using Composite Materials, *International Journal of Advances in Scientific Research and Engineering*, 4(11): 21 - 28
- Letam, L. P., Charles, K., and Terence, T. T. W., (2018). Influence of Waste Agricultural Fibre Products Material and Lime on Geotechnical Characteristics of Expansive Soils, *International Journal of Advances in Scientific Research and Engineering*, 4(11): 49 - 57
- Mallela, J., Harold, P. V. Q., Smith, K. L. and E. Consultants., (2004). Consideration of Lime-Stabilized Layers in Mechanistic-empirical Pavement Design. The National Lime Association, Arlington, Virginia, USA
- Ola, S. A. (1974). Need for Estimated Cement Requirements for Stabilizing Lateritic Soils. *Journal of Transportation Engineering, ASCE*, 100(2):379–388.

Omotosho, P. O. (1993). Multi-Cyclic Influence on Standard Laboratory Compaction of Residual Soils. *Engineering Geology*, 36, 109–115.

Omotosho, P. O. and Akinmusuru, J. O. (1992). The behavior of Soils (Lateritic) Subjected to Multi-Cyclic Compaction. *Engineering Geology*, 32, 53–58

Sabat, A. K. (2012). Effect of Polypropylene Fiber on Engineering Properties of Rice Husk Ash – Lime Stabilized Expansive Soil, *Electronic Journal of Geotechnical Engineering*, 17(E), 651-660

Sharma, R.S., Phanikumar, B. R. and Rao, B.V. (2008). Engineering Behaviour of a Remolded Expansive Clay Blended with Lime, Calcium Chloride and Rice-Husk Ash, *Journal of Materials in Civil Engineering*, 20(8): 509-515

Terence, T. T. W., Charles, K., Amakiri – Whyte, B., (2018). Performance Characteristics of Cement, Lime - Pozzolanic Bagasse Fibre Ash Stabilized Expansive Lateritic Soils for Highway Pavement Materials. *International Journal of Scientific & Engineering Research*, 9(12): 1092 – 1109.

Viswanadham, B.V.S., Phanikumar, B. R and Mukherjee, R.V. (2009). Swelling Behavior of a Geofiber-Reinforced Expansive Soil. *Geotech. Geomembranes*, 27(1): 73-76.

Yang, G., Liu, H., P. L. and Zhang, B. (2012). Geogrid-Reinforced Lime-Treated Cohesive Soil Retaining Wall: Case study and implications. *Geotext. Geomembranes*, 35(0): 112-118.

