REFERENCES

Armand, M. and Tarascon, J.M. (2008). Building Better Batteries, Nature, 451(7179),652.-657.

Bin, L., Tao, L., Guangyuan, M., Xianfu, 'N., Di, C. and Guozhen, S. (2013). Rechargeable Mg-Ion Batteries Based on WSe2 Nanowire Cathodes, American Chemical Society Publications, 7(9), 8051- 8058.

Ichitsubo, T'., Adachi, T., Yagi, S. and Dci, T. (2011). Potential Positive Electrodes for High-Voltage Magnesium-ion Batteries. Journal of Materials Chemistry.111-114.

Maduelosi,N.J,Abia,A.Aand Nwokobia,F.U (2014) characterization of mixed solvents of tetrahydrofuran and acetonitrile for magnesium ion battery. Journal of chemistry and material research 6(12),188-192.

Motin, M.A. (2007). Temperature and Concentration Dependence of Apparent Molar Volumes and Viscosities of NACLI NH4CL, CUCL4, COSO4, and MGSO4 in Pure Water and Water + Urea Mixtures. Journal of chemical Engineering Data, 49,94-98.

Nageshewar, D. and Anil, K. (2010). Ionic Liquids; New Materials with Wide Applications. Indian Journal .of Chemistry,

49A,635-648.

Nwokobia,F.U, Cookey,G.A and Abia,A.A(2013). Effect of salt concentration on the conductivity and viscosity of binary mixture electrolyte solution. Journal of applied chemistry 8(2)35-41.

Obunwo C. and Izonfuo, W.A.L (1999).Binary mixture on conductance of Acetonitrile and Propylene carbonate, J.chem. vol.919-942(5) 152-156.

Rodriguez, A., Canosa, J., Dominguez, A. and Tojo, J. (2003). Viscosities of Dimethyl Carbonate or Diethyl Carbonate with Alkanes at Four Temperatures. New UNFAC-VISCO Parameters. Journal of Chemical Engineering Data, 48 ,146-151