

- using Finite Element Method Simulation, Machining Science and Technology, Vol. 6, PP. 467-486.
5. Outeiro, J. C., Pina, J. C., M'saoubi, R., Pusauec, .F and Jawahir, I.S. (2008) Analysis Of Residual Stresses Induced by Dry Turning of Difficult-To-Machine Materials. CIRP Annals – Manufacturing Technology, Vol. 57, Pp. 77-80.
 6. Altan, T. and Semiatim (2012) Measurement and Interpretation of Flow Stress Data for the Simulation of Metal-Forming Processes. Air Force Research Laboratory, Materials and Manufacturing Directorate, Ohio. The Ohio State University Columbus, Oh.
 7. Grzesik and Wanat (2006) Influence of Tool Wear on Surface Roughness in Hard Turning using different Shaped Ceramic Tools Wear, Vol. 265, PP. 327-335.
 8. Chou, K. Y., Evans, J. C. and Barash, M. M. (2002) Experimental Investigation on CBN Turning of Hardened AISI 52100 Steel. Journal of Materials Processing Technology, Vol.124, PP. 274-283.
 9. Benga, G. C and Abrao, A. M. (2013)Turning of Hardened 100 Cr 6 Bearing Steel with Ceramic and PCBN Cutting Tools. Journal of Materials Processing Technology, Vol.143-144, PP. 237-241.
 10. Grzesik and Wanat (2006) Influence of Tool Wear on Surface Roughness in Hard Turning using different Shaped Ceramic Tools Wear, Vol. 265, PP. 327-335.
 11. Collins Eruogun Etin-osa and Joseph Ifeanyi Achebo. (2017). Analysis of Optimum Butt Welded Joint for Mild Steel Components Using FEM (ANSYS). American Journal of Naval Architecture and Marine Engineering DOI: 10.11648/j.aas.20170206.12
 12. Ozel, Trugrul, And Taylan, Altan. (2000) Determination of Work Piece Flow Stress and Friction at the Chip-Tool Contact for High-Speed Cutting. International Journal of Machine Tools and Manufacture, Vol. 40, PP. 133-152.
 13. Aberg, E. and Green, R.E (1996) Machinery's Handbook 25th Edition Industrial Press Inc. New York.
 14. Walter, A.G (1996) Tungsten Carbide Tools General Catalogue, Trade Catalogue, Tubingen.
 15. Thomas, M., Beauchamp Y, Youssef, Y.A, Masounave, J. (1997). An Experimental design for surface roughness and built-up edge formation in lathe dry turning. Int. J. Qual. Sci. 2(3), PP. 167-180.