

CONCLUSION

- The Direct Shear test can be used as an alternative method of determining the Soil type of soil samples.
- The Direct Shear test is an economical method of determining soil parameters since it can both determine the soil shear strength and the soil type compared to other existing methods that only yields the soil texture of soil sample (hydrometer method, The pi-pet method, Feel method, etc.).

REFERENCES

D. Bro, J. P. Stewart, and D. Pradel, Estimating Undrained Strength of Clays from Direct Shear Testing at Fast Displacement Rates, Proceedings of ASCE Geotronics, 2013.

American Society for Testing and Materials, Designation: D, 3080/D, 3080M-11, Standard Test Method for Direct Shear Test of Soils under Consolidated Drained Conditions, vol. 4.08 of Annual Book of ASTM Standards, 2011.

Koloski, J.W., S.D. Schwarz, D.W. Tubbs, 1989. Geotechnical properties of geologic materials. Engineering Geology in Washington, Washington Division of Geology and Earth Resources Bulletin 78(1).

Lindeburg, M.R., Civil engineering reference manual for the PE exam. Professional Publications, Incorporated. 8th Edition.

https://elibrary.asabe.org/data/pdf/7/sd2009/chap3_cdfiles/Guidelines_for_spreadsheets.pdf